

**SAFETY DATA SHEET** 

V120 WASH

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier				
Product code	:	KV101VWG01		
Product name	:	V120 WASH		
1.2 Relevant identified uses of	<u>the s</u>	substance or mixture and uses advised against		
Product use	:	Roller and blanket wash for lithographic printing		
Uses advised against	:	None known.		
1.3 Details of the supplier of the safety data sheet				
Manufacturer / Distributor	:	Print Media Europe, Varn House, Northbank Industrial Park, Irlam, Greater Manchester, M44 5BL England.		
e-mail address of person responsible for this SDS	:	MSDS.UnitedKingdom.Irlam.TM@flintgrp.com		
1.4 Emergency telephone numb	er (w	vith hours of operation)		

#### 1.4 Emergency telephone number (with hours of operation)

+44 (0) 333 333 9879 (8:00 h - 17:00 h)

<u>History</u>	
Dete	

<u> </u>		
Date of printing	:	09.11.2017.
Date of issue/ Date of revision	:	17.05.2017.
Date of previous issue	:	06.09.2016.
Version	:	2.01

# **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

AMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms



Signal word	: Danger
Hazard statements	: ₩226 - Flammable liquid and vapor.
	H304 - May be fatal if swallowed and enters airways.
	H335 - May cause respiratory irritation

- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

# **SECTION 2: Hazards identification**

Precautionary statements	:	<ul> <li>P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or physician.</li> <li>P403 + P233 - Store container tightly closed in well-ventilated place.</li> <li>P210 - Keep away from flames and hot surfaces No smoking.</li> <li>P370 + P378 - In case of fire: Use alcohol-resistant foam to extinguish.</li> <li>P331 - Do NOT induce vomiting.</li> <li>P501 - Dispose of contents and container in accordance with all local, regional,</li> </ul>
		national and international regulations. P405 - Store locked up.
Supplemental label elements	:	Repeated exposure may cause skin dryness or cracking.
Hazardous ingredients	:	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.

2.3 Other hazards

PBT

vPvB

- : P: Not available. B: Not available. T: Not available.
- : vP: Not available. vB: Not available.

# **SECTION 3: Composition/information on ingredients**

- 3.2 Mixtures
- : Mixture

Product/ingredient name	Identifiers	%	<u>Classification</u> Regulation (EC) No. 1272/2008	Туре
	lucitations	70	[CLP]	турс
<ul> <li>✓ydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics,</li> <li>&lt;2% aromatics</li> </ul>	REACH #: 01-2119463258-33 EC: 919-857-5 CAS: 64742-48-9 (CAS valid outside EU) Index: 649-327-00-6	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	[1]
Solvent naphtha (petroleum), light arom.	REACH #: 01-2119486773-24 EC: 265-199-0 CAS: 64742-95-6 Index: 649-356-00-4	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
(2-methoxymethylethoxy) propanol	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤10	Not classified.	[2]
Hydrocarbons, C12-C15, n- alkanes, isoalkanes < 2% aromatics	REACH #: 01-2119453414-43 EC: 920-107-4 CAS: 64742-47-8 (CAS valid outside EU) Index: 649-422-00-2	≤3	Asp. Tox. 1, H304 EUH066	[1]
2,6-ditert-butyl-p-cresol	REACH #: 01-2119565113-46 EC: 204-881-4 CAS: 128-37-0	≤0.3	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]

# SECTION 3: Composition/information on ingredients

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

4.1 Description of first aid mea	asures	
General	:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention/advice.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Give nothing by mouth. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
Use suitable protective equipn	nent (s	ection 8).
4.2 Most important symptoms	and et	ffects, both acute and delayed
See toxicological information (	Sectio	n 11)

See toxicological information (Section 11)

4.3 Indication of any	<u>r immediate medical attention and s</u>	pecial treatment needed
		-

Notes to physician	reat symptomatically. Contact poison treatment specialist uantities have been ingested or inhaled.	immediately if large
Specific treatments	o specific treatment.	

## **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable Extinguishing media	:	Recommended:, alcohol-resistant foam, CO <sub>2</sub> , powders, water spray
Extinguishing media not to be used	:	Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	:	Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
		Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
		Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **6.2 Environmental precautions**

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and materials for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information. See Section 13 for additional waste treatment information. See Section 8 for information on appropriate personal protective equipment.

# SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Remove contaminated clothing and protective equipment before entering eating areas. Workers should wash hands and face before eating, drinking and smoking. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with all local, regional, national and international regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Observe label precautions. Keep container tightly closed and in a well-ventilated place. Keep away from sources of ignition - No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Seveso Directive - Reporting thresholds (in tonnes)

#### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
<b>P</b> 5c: Flammable liquids 2 and 3 not falling under P5a or P5b E2: Hazardous to the aquatic environment - Chronic 2	5000 200	50000 500
6: Flammable (R10) 9ii: Toxic for the environment	5000 200	50000 500

#### 7.3 Specific end use(s)

Not applicable.

### 7.4 Additional information

Not applicable.

## SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Ingredient name	Occupational expos	ure limits
(2-methoxymethylethoxy)propar	ol <b>EH40/2005 WELs (U</b> through skin. TWA: 308 mg/m³ 8 ł TWA: 50 ppm 8 hou	
Other Exposure limits :	CMR: See toxicological information (S	ection 11)
Recommended monitoring : procedures	atmosphere or biological monitoring m of the ventilation or other control meas protective equipment. Reference shou the following: European Standard EN the assessment of exposure by inhalat limit values and measurement strategy atmospheres - Guide for the applicatio of exposure to chemical and biological (Workplace atmospheres - General re- for the measurement of chemical ager	quirements for the performance of procedures
Date of issue/Date of :	17.05.2017.	Page: 5/1

# **SECTION 8: Exposure controls/personal protection**

required.

### **DNELs/DMELs**

No DNELs/DMELs available.

### PNECs

No PNECs available.

#### 8.2 Exposure controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Respiratory protection	:	Sased on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Gloves	:	For prolonged or repeated handling, use the following type of gloves:
		May be used: nitrile rubber, neoprene
Other skin protection		Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Eye/face protection	:	Use safety eyewear designed to protect against splash of liquids.
Environmental exposure cont	rols	

Do not allow to enter drains or watercourses.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Color	: Yellow.
Odor	: Hydrocarbon.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Boiling point	: >= 150 °C
Flash point	: Closed cup: 45°C [Measured]
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not applicable.
Burning time	: Not applicable.
Burning rate	: Not applicable.

: 17.05.2017.

## **SECTION 9: Physical and chemical properties**

Explosion limits		
Lower:	:	1 %Vol
Upper:	:	14 %Vol
Vapor pressure	:	< 4 hPa
Vapor density	:	Not available.
Density	:	~ 0.8 g/cm³
Solubility	:	Soluble in water in any proportion.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	ca 200 °C
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): <0.06 cm <sup>2</sup> /s (<6 cSt)
Explosive properties	:	Not available.
Oxidizing properties	:	Not available.
9.2 Other information		
CADT	-	Natauallahla

SADT

Not available.

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Not available.

#### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see Section 7).

### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame).

#### 10.5 Incompatible materials

Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids

### 10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

÷

### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Ingestion may cause gastrointestinal irritation and diarrhea. If splashed in the eyes, the liquid may cause irritation and reversible damage.

#### Substances / Mixtures

Product/ingredient name	Result	Species	Dose	Exposure
Solvent naphtha (petroleum), light arom.	LD50 Oral	Rat	8400 mg/kg	-

# **SECTION 11: Toxicological information**

### Acute toxicity estimates

Not available.

Irritation/Corrosion	:	Irritating to respiratory system.		
Sensitization	:	Not available.		
Mutagenicity	:	Not available.		
Carcinogenicity	:	Not available.		
Reproductive toxicity	:	: Not available.		
Specific target organ toxicity (single exposure)	:	Not available.		
Specific target organ toxicity (repeated exposure)	:	Not available.		
Aspiration hazard	:	Aspiration hazard if swallowed. Can enter lungs and cause damage.		
Chronic toxicity	:	Not available.		
Teratogenicity	:	Not available.		
Other information				
Toxicokinetics				
Absorption	:	Not available.		
Distribution	:			
Metabolism	:	Not available.		
Elimination	:	Not available.		

# **SECTION 12: Ecological information**

There are no data available on the mixture itself. This material is toxic to aquatic life with long lasting effects. Do not empty into drains or watercourses. See Sections 2 and 3 for details.

### 12.1 Toxicity

Not available.

#### 12.2 Persistence and degradability

Not available.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Solvent naphtha (petroleum), light arom.	-	10 to 2500	high
0	0.0043	-	low
2,6-ditert-butyl-p-cresol	5.1	1071.52	high

#### 12.4 Mobility in soil

Not available.

### 12.5 Results of PBT and vPvB assessment

PBT

: P: Not available. B: Not available. T: Not available.

vPvB

- : vP: Not available. vB: Not available.
- 12.6 Other adverse effects

# SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

Yes.

: The generation of waste should be avoided or minimized wherever possible. Methods of disposal Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### Hazardous waste 5

#### European waste catalogue (EWC)

Waste code	Waste designation
07 07 04*	other organic solvents, washing liquids and mother liquors

## **SECTION 14: Transport information**

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### International transport regulations

<u>14.1 UN number</u>	:	UN3295
14.2 Proper shipping name	:	HYDROCARBONS, LIQUID, N.O.S.
14.3 Transport hazard class(es)	:	3



14.4 Packing group	:	III
14.5 Environmental hazards	:	Hazardous to aquatic environment
14.6 Special precautions for	:	Not applicable.
<u>user</u>		
14.7 Transport in bulk accord	<u>ing to</u>	Annex II of MARPOL and the IBC Code
Not applicable.		
Additional information		
ADR ADN		
Classification code	:	F1
Special provisions	:	Not available.
Hazard identification number	:	30
ADR Tunnel Code:	:	(D/E)
Limited quantity	:	5 L
IMDG		
Emergency schedules (EmS)	:	F-E, S-D
Marine pollutant	:	Yes.
Marine pollutant substances	:	Solvent naphtha (petroleum), light arom.
Limited quantity	:	51
IATA		Max. Qty Packaging instruction
Passenger and Cargo Aircraft	:	60 L 355
Date of issue/Date of revision	: 17	7.05.2017.

Conforms to Regulation (EC) No.	13	0//2006 (REAC	, Annex n
V120 WASH			
<b>SECTION 14: Transport</b>	ir	formation	l
Cargo Aircraft Only	:	220 L	366
Limited quantity	:	10 L	Y344
SECTION 15: Regulator	y i	informatior	n
15.1 Safety, health and environm	ent	al regulations/l	/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2	200	<u>6 (REACH)</u>	
Annex XIV - List of substances	s si	ubject to author	<u>prization</u>
Annex XIV			
None of the components are liste	ed.		
Substances of very high conc	ern	L	
None of the components are liste	ed.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.	
VOC content	:	~ 96 %	~ 787.2 g/L
Europe inventory	:	All components	ts are listed or exempted.
National regulations			
Industrial use	:	user's own asse safety legislatio	on contained in this safety data sheet does not constitute the sessment of workplace risks, as required by other health and on. The provisions of the national health and safety at work ply to the use of this product at work.

### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

# **SECTION 16: Other information**

CEPE MSDS Code	: 1
Indicates informat	ion that has changed from previously issued version.
Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
✓am. Liq. 3, H226	On basis of test data
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method
Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 2, H411	Calculation method

#### **V120 WASH SECTION 16: Other information** Full text of abbreviated H H226 : Flammable liquid and vapor. May be fatal if swallowed and enters airways. H304 statements H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. H410 H411 Toxic to aquatic life with long lasting effects. 11/9/2017 • Date of printing Date of issue/ Date of : 5/17/2017 revision Date of previous issue : 9/6/2016 Version : 2.01

#### Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.