

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 product identifier**

Product code : VP10049D01
 Product name : NOVACOAT 4433; SM 2,5KG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Printing ink or Additive
 Uses advised against : None known.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Distributor : Flint Group UK Ltd
 Old Heath Road
 GB Wolverhampton
 WVI 2QT
 UNITED KINGDOM

e-mail address of person responsible for this SDS : compliancecentre@flintgrp.com

1.4 Emergency telephone number (with hours of operation)

+44 (1902) 87 10 28 (8:00 h - 17:00 h)

History

Date of printing : 06.11.2012.
 Date of issue/ Date of revision : 03.09.2012.
 Date of previous issue : 29.09.2010.
 Version : 7

2. HAZARDS IDENTIFICATION**Classification and labeling according to Regulation (EC) 1907/2006 (REACH)**

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

2.1b Classification of the substance or mixture

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R52/53
 Physical/chemical hazards : Not applicable.
 Human health hazards : Not applicable.
 Environmental hazards : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2b Label elements

Hazard symbol or symbols :

Risk phrases : R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases : S60- This material and its container must be disposed of as hazardous waste.

Contains :

Additional warning phrases and Additional information

Contains cobalt(II)-2-ethylhexanoate. May produce an allergic reaction.

2.3 Other hazards which do not result in classification

Results of PBT and vPvB assessment: See sections 12 for details.

NOVACOAT 4433; SM 2,5KG

3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures**

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name	%	REACH Registration number	CAS number	EC number	Classification
distillates (petroleum), hydrotreated light paraffinic	25-35		64742-55-8	265-158-7	Xn; R65 R66 [1]
distillates (petroleum), acid-treated middle	<10		64742-13-8	265-113-1	Xn; R65 R66 [1]
cobalt(II)-2-ethylhexanoate	0.1-1		136-52-7	205-250-6	R43 N; R50/53 [1]

See section 16 for the full text of the R-phrases declared above

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

Hazardous ingredients / Classification according to Regulation (EC) 1272/2008 (CLP)

Chemical name	CAS number	Hazard statements	Classification
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Harmful if inhaled. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking.	ACUTE TOXICITY: INHALATION - Category 4 ASPIRATION HAZARD - Category 1
distillates (petroleum), acid-treated middle	64742-13-8	May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking.	ASPIRATION HAZARD - Category 1
cobalt(II)-2-ethylhexanoate	136-52-7	May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects.	SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 1 AQUATIC TOXICITY (CHRONIC) - Category 1

4. FIRST AID MEASURES**4.1 Description of first aid measures**

- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention/advice.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Give nothing by mouth. Do NOT induce vomiting.

Use suitable protective equipment (section 8).

4.2 Most important symptoms and effects, both acute and delayed

See toxicological information (section 11)

4.3 Indication of any immediate medical attention and special treatment needed

NOVACOAT 4433; SM 2,5KG

4. FIRST AID MEASURES

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media : Recommended:, alcohol-resistant foam, CO₂, powders, water spray

Extinguishing media not to be used : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for fire-fighters

Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area.

Avoid breathing vapor or spray. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and materials for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep container tightly closed. Avoid contact with skin and eyes. Avoid inhalation of vapor, spray or mist. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see section 8). Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with all local, regional, national and international regulations.

Store in a dry, cool and well-ventilated area, away from incompatible materials (see section 10).

Observe label precautions. Keep container tightly closed and in a well-ventilated place.

Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature: 5 to 35°C

7.3 Specific end use(s)

Not applicable.

7.4 Additional information

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

NOVACOAT 4433; SM 2,5KG

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters**

Ingredient name	Occupational exposure limits
cobalt(II)-2-ethylhexanoate	EH40/2005 WELs (United Kingdom (UK), 8/2007). Skin sensitizer. Notes: as Co TWA: 0.1 mg/m ³ , (as Co) 8 hour(s).

Other Exposure limits : CMR: See toxicological information (section 11)

8.2 Exposure controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Respiratory system : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Skin and body : Personnel should wear protective clothing.

Hands : The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

For prolonged or repeated handling, use the following type of gloves:

Recommended:
4-8 hours: polyethylene (PE) or Viton gloves.

References: <http://www.esig.org/en/library/publications/best-practice-guides>

Eyes : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties****Appearance**

Physical state : Liquid.

Color : Colorless.

Odor : Hydrocarbon.

Odor threshold : Not available.

pH : Not available.

Melting point : Not available.

Boiling point : >= 200 °C

Flash point : Closed cup: > 100°C [Measured]

Evaporation rate : Not available.

Flammability (solid, gas) : Not applicable.

Burning time : Not applicable.

Burning rate : Not applicable.

Explosion limits

Lower: : Not available.

Upper: : Not available.

Vapor pressure : < 0.1 hPa

Vapor density : Not available.

Density : ~ 1 g/cm³

Solubility : insoluble in water.

NOVACOAT 4433; SM 2,5KG

9. PHYSICAL AND CHEMICAL PROPERTIES

Octanol/water partition coefficient	: Not available.
Auto-ignition temperature	: ca 343 °C
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.07 cm ² /s (>7 cSt)
Explosive properties	: Not available.
Oxidizing properties	: Not available.

9.2 Other information

SADT	: Not available.
------	------------------

10. STABILITY AND REACTIVITY

10.1 Reactivity

Not available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Not available.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials

Keep away from the following materials to prevent strong exothermic reactions:
oxidizing agents, strong alkalis, strong acids

10.6 Hazardous decomposition products

Decomposition products may include the following materials:
carbon monoxide, carbon dioxide, smoke, oxides of nitrogen

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 3 for details.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Substances / Mixtures

Acute toxicity :

Product/ingredient name	Result	Species	Dose	Exposure
distillates (petroleum), hydrotreated light paraffinic	LC50 Inhalation Dusts and mists	Rat	3900 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Irritation/Corrosion	: Not available.
Sensitization	: Contains Sensitizing material . May produce an allergic reaction. See sections 2 and 3 for details.
Mutagenicity	: Not available.
Carcinogenicity	: Not available.
Reproductive toxicity	: Not available.

NOVACOAT 4433; SM 2,5KG

11. TOXICOLOGICAL INFORMATION

Specific target organ toxicity (single exposure) : Not available.

Specific target organ toxicity (repeated exposure) : Not available.

Aspiration hazard : Not available.

Chronic toxicity : Not available.

Teratogenicity : Not available.

Product name	List name	Name on list	Classification	Notes
cobalt(II)-2-ethylhexanoate	UK Occupational Exposure Limits EH40 - WEL	cobalt compounds	Carc.	

Other information**Toxicokinetics**

Absorption : Not available.

Distribution : Contains material which causes damage to the following organs: eye, lens or cornea.
Contains material which may cause damage to the following organs: upper respiratory tract.

Metabolism : Not available.

Elimination : Not available.

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See sections 3 and 15 for details.

12.1 Toxicity data

Not available.

12.2 Persistence/degradability

Not available.

Product/ingredient name	Test	Result	Dose	Inoculum
cobalt(II)-2-ethylhexanoate		- % - Not readily - - days	-	-

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Not available.

12.5 Results of PBT and vPvB assessment

PBT : P: Not available. B: Not available. T: Not available.

vPvB : vP: Not available. vB: Not available.

12.6 Other adverse effects

AOX : Not available.

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.

NOVACOAT 4433; SM 2,5KG

13. DISPOSAL CONSIDERATIONS

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European waste catalogue (EWC)** : The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 03 12* waste ink containing dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.
- Hazardous waste** : Yes.

14. TRANSPORT INFORMATION

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

International transport regulations

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

14.1 UN number : Not applicable.

14.2 Proper shipping name : Not applicable.

14.3 Transport hazard class(es) : Not applicable.

14.4 Packing group : Not applicable.

14.5 Environmental hazards : Not applicable.

14.6 Special precautions for user : Not applicable.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Other Special Considerations about the Product:

Materials such as cleaning rags, paper wipes etc, which are contaminated with coldset ink need not be assigned to ADR class 4.2, provided they are transported in containers of less than 450 liters capacity (ADR 2.2.42.1.5(c), Note 2). This exemption does not apply if contaminated materials are mixed with other wastes.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- EU regulations** : The product is classified as dangerous according to Directive 1999/45/EC and its amendments.
See sections 2 and 3 for details.
- VOC content** : < 1 %
- Europe inventory** : All components are listed or exempted.
- Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

NOVACOAT 4433; SM 2,5KG

16. OTHER INFORMATION

CEPE MSDS Code : 8

Full text of R-phrases referred to in sections 2 and 3 - Europe

R65- Harmful: may cause lung damage if swallowed.

R43- May cause sensitization by skin contact.

R66- Repeated exposure may cause skin dryness or cracking.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The information in this Safety Data Sheet is required pursuant to Annex II to Regulation (EC) No 1907/2006.

Date of issue/Date of revision : 03.09.2012.

Version : 7

☑ Indicates information that has changed from previously issued version.

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.